EUROCAVE[®]

THE CHAMPAGNE CABINET

Large size

Manufactured in France 1-temperature cabinet

YEAR WARRANTY Single-temperature cabinet, for serving or ageing

champagne

Technical specifications

Equipment	
Standard shelves	






5 bottles 10kg

~

Fixed presentation shelf APRESCHAMPG 8 bottles 12kg



Sliding presentation shelf ACCHAMPG 8 bottles of champagne 6 magnum of champagne 4.8kg



Presentation LUX pack standard 1 fixed presentation shelf +7 sliding shelves 75 bottles

) I II		Т
i	1950	٦Ĺ
đ	1 A	٦Ĭ,
đ	THE I	Ĩ
đ	1951	Ĵ,
đ	1 M	Ĩ
đ	1941	7
đ	5	٦Ï,
đ	1951	٦,
đ	1951	٦Ĭ,
đ	95	٦Ĭ,
Æ	999	ð
		-

Premium pack 10 sliding shelves 91 bottles



Presentation LUX pack magnum 1 fixed presentation shelf + 6 sliding shelves 62 bottles

Capacity	91 bottles maximum*	
Temperature	• Default setup temperature: 5°C / 41° • Temperature setting range from 5°C	
Design	 Full Glass door Reversible door (warning on the orientation of the icotype on the handle) Removable Full glass handle Central lock Champagne coloured control panel with glossy finish White screen display 	 LED screen with touch-sensitive keys 1 ambient light, amber, blue or red (colour to be selected on order) 3 lighting options: permanent, on door opening or off
Accessories	 1 sliding presentation shelf, equipped with a soft close system. 8 removable bottle holders, in brushed stainless steel 2 fixed presentation shelves (standard or magnum bottles). 8 or 5 polished stainless steel bottle holders 	 Shelves with champagne- coloured lacquer fronts Shiny leather finish to protect bottles and for more comfort of use 1 microfibre cloth 1 erasable felt-tip marker 1 EuroCave keyring
Equipment	• Charcoal filter • Clay ball humidity cassette	• 2 adjustable feet at the front • Condensate drip tray at the back
Regulation	 Electronic regulation Display of the real temperature inside the cellar Display of the humidity when the temperature is set between 9-12°C/ 48-54°F 	 Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm) Automatic defrost
Technologies	Cold production: Cords: Heat production: Heatt release: Inner material: Exterior coating material: Insulation type:	Air fan/Compressor R600a CE/US/UK/JA/AU/CH/C6 Heating element Automatic/threshold:adjustable Aluminium HDF (High Density Fibreboard) PU foam (59mm)

*Standard champagne format

General features

	Full Glass door
Gross weight packaged (kg)	96
Weight of reinforced packaging (kg)	13 (+8 kg pallet)
Dimensions H x W x D (mm)	1825 x 680 x 720**
Dimensionsin pack H x W x D	1950 x 720 x 760
Color	Nero - RAL 9005

**With rear stopper, without handle

Energy efficiency and consumption

Cords	230V-50Hz (R600a)	115V-60Hz (R600a)
Type of door	Full Glass	Full Glass
Energy efficiency class	G	G
Annual energy consumption (kWh/ year)	190	190
Sound emission (dB(A))	37	37
Sound emission class	С	С
Ambient operating temperatures (C°/°F)	0-30°C / 32-86°F	0-30°C / 32-86°F
Useful volume (litres)	461	

The champagne cabinet, in a few words...

The French way of life

The champagne cabinet is exclusively dedicated to displaying and serving champagne, it is a one-of-akind object. Designed to store all shapes and sizes of champagne bottles thanks to its specially designed shelves, this cabinet is a bold

homage to the originality of champagne houses and their heritage.



